



RECEIVED

OCT 29 2002

GROUP 3600

PATENT
Attorney Docket No. 187627

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Al Mitrevics

Application No. 09/468,501

Filed: 12/21/99

For: GLAZING SYSTEM FOR HOLLOW METAL
WALLS

Art Unit: 3637

Examiner: Dennis Dorsey

**AMENDMENTS TO CLAIMS
MADE IN RESPONSE TO OFFICE ACTION DATED JULY 17, 2002**

Amendments to existing claims:

1. A bent metal glazing bead formed of pressed steel sheet material having at least one elongated leg that has at least one portion thereof of a u-shaped cross-section where one side of the u-shape is short and the other side is long and includes a bridge portion, the elongated u-shaped cross-section and bridge portion forming a bead, the elongated u-shaped leg with its long side and bridge portion providing a smooth continuous surface,

the elongated u-shaped cross-section leg configured to cooperate in a mating fashion with a portion of a support structure to sandwich a panel on the support structure between the short side of the elongated leg and long side bridge portion and an opposing surface portion of the support structure to thereby glaze the panel in place and simultaneously visually present a smooth continuous surface of the glazing bead to mask a junction of the panel with the support structure.

5. A bent metal glazing bead formed of pressed steel sheet material having a pair of spaced elongated legs having an inside U-shaped channel therebetween, each leg having portions thereof that have a U-shaped hollow cross-section, one side of each U-shape leg portion being short and the other side being long and said sides being interconnected to form said hollow cross-section, a bridge element joining the spaced apart elongated legs so as to

In re Appln. of Al Mitrevics
Application No. 09/468,501

provide an outside continuous surface spanning both elongated legs and the inside U-shaped channel;

the U-shaped inside channel of the glazing bead configured to cooperate in a mating fashion with a portion of a mullion to sandwich panels on either side of the mullion between the elongated legs and an opposing surface portion of the mullion to thereby simultaneously glaze both side of the mullion and thereby present the smooth continuous outside surface of the glazing channel to mask a junction of the panels with the mullion.